




# **AP43-HTS Condensate Pump Technical Information**

#### **Dimensions:**









Pump is certified to CAN/CSA STD C22.2 no. 108 4007096 Pump conforms to ANSI/UL STD 778

**Tank:** 3.8 Litre

**Weight:** 3.13 kg, 6.90 lbs (empty)

6.6 kg, 14.6 lbs (full)

#### **Electrical:**

Pump: 120 VAC 60Hz, 226W, 1.91 Amps High level safety switch rating: 125 or 250VAC 6A, 125V DC 0.4A, 250V DC 0.3A

### **Pump Performance:**

Submerged pump is self-priming 282 L/hr (74 gph) @ free flow 123 L/hr (32 gph) @ 7 m (23ft)

#### **AP43-HTS Pump Curve** 45 40 35 30 Head (ft.) 25 20 15 10 5 0 0 50 200 100 150 Flow Rate (U.S. GPH)

## **Specifications:**

The condensate pump shall be AXIOM INDUSTRIES LTD. Model AP43-HTS. System shall include 3.5 litre (0.9 U.S. gallon) tank made and lid made from ABS, pump with thermal cut-out and electrically certified to CAN/CSA STD C22.2 no. 108 conforms to ANSI/UL STD 778; low level float switch; high level float switch with N.C. or N.O. contacts (factory set to N.C.) for remote alarm system; check valve; 6 ft. long power cord. Power supply 120/60/1.91A.

#### LIMITED WARRANTY

The "AP43-HTS" is warranted against defects in materials and workmanship for two years.

### **Project Details:**

Project	Location
Consultant	Contractor
Unit Tag	Sales Agent

SB-AP43-HTS-01